

T 13-125 (600431420) Diamond Cutting System MetaLoc

Order no. 600431420 EAN 4061792176164



Representative picture









- Compact diamond cutter for low-dust dry cuts up to 27 mm in mineral-based materials
- Efficient dust extraction for health protection and clean construction sites
- Metabo Long-life motor with patented dust protection for long service life
- Suitable for universal use with pushing cuts and plunge function
- Precise cuts in even surfaces thanks to metal base plate with rollers, removable for free-handed cutting
- Usable with guide rails for long, straight cuts
- Safety and control in every situation: S-automatic safety clutch and restart protection
- Extraction hood can be mounted tool-free, made of anti-static plastic
- Auto-stop carbon brushes to protect the motor
- Connection for dust extraction Ø 1-1/2"

www.metabo.com 1 / 2



Technical values	
Parameters	
Amps	12 AMPS
Cutting disc Ø	5 "
Max. cutting depth	1 1/16 "
Rated input power	1350 W
Output power	830 W
No-load speed	9600 RPM
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	5.5 lbs
Cable length	8 ft
Vibration	
Vibration	5.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Spanner wrench

Inner support flange

Nut with two holes

Side handle Metabo VibraTech (MVT)

www.metabo.com 2/2