

## WEV 15-150 HT (600563420) Angle Grinder Cardboard box; with speed control

Order no. 600563420  
EAN 4007430320353



Representative picture



- Optimum processing of stone: robust, powerful angle grinder with gear reduction and reduced, adjustable speed for material-friendly working
- Longer service life, more drive: the Metabo Marathon-Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### Parameters

Amps	13.5 AMPS
Disc diameter	6 "
Rated input power	1550 W
Output power	900 W
No-load speed	2000 - 7600 RPM
Speed at rated load	7600 RPM
Torque	44 in-lbs
Spindle thread	5/8" - 11 UNC
Grip circumference	8 1/8 "
Weight (without power cable)	5.7 lbs
Cable length	8 ft

### Vibration

Surface grinding	4.7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Polishing	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
 Inner support flange  
 Nut with two holes  
 Side Handle  
 Spanner wrench