

WEPBA 17-125 Quick RT DS (600605420) Angle Grinder Cardboard box

Order no. 600605420
EAN 4007430320278



Representative picture



- Maximum productivity through strong power at a low weight
- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Perfect ergonomics thanks to a slim grip area for maximum control and easily working overhead
- Metabo LongLife Motor with new cooling and carbon brush system for double the service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for disc change without tools at the push of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibration for fatigue-free work with Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest user safety with patented, mechanical disc brake and deadman switch: disc stops in 2 seconds after release, even during a power failure
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical values

Parameters

| | |
|------------------------------|---------------|
| Amps | 14.5 AMPS |
| Disc diameter | 5 " |
| Output power | 1000 W |
| No-load speed | 10000 RPM |
| Speed at rated load | 10000 RPM |
| Torque | 34 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Grip circumference | 5.438 " |
| Weight (without power cable) | 6 lbs |
| Cable length | 8 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 6.1 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 4.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 92 dB(A) |
| Sound power level (LWA) | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
 Inner support flange
 M-Quick flange nut
 Side handle Metabo VibraTech (MVT)