

## WEPBA 17-150 Quick RT DS (600606420) Angle Grinder

### Cardboard box

Order no. 600606420  
EAN 4007430320261



Representative picture



- Maximum productivity through strong power at a low weight
- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Perfect ergonomics thanks to a slim grip area for maximum control and easily working overhead
- Metabo LongLife Motor with new cooling and carbon brush system for double the service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for disc change without tools at the push of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibration for fatigue-free work with Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest user safety with patented, mechanical disc brake and deadman switch: disc stops in 2 seconds after release, even during a power failure
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### Parameters

|                              |               |
|------------------------------|---------------|
| Amps                         | 14.5 AMPS     |
| Disc diameter                | 6 "           |
| Output power                 | 1000 W        |
| No-load speed                | 9600 RPM      |
| Speed at rated load          | 9600 RPM      |
| Torque                       | 39 in-lbs     |
| Spindle thread               | 5/8" - 11 UNC |
| Grip circumference           | 5.438 "       |
| Weight (without power cable) | 6 lbs         |
| Cable length                 | 8 ft          |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 6 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 4.9 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LwA)      | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Guard  
 Inner support flange  
 M-Quick flange nut  
 Side handle Metabo VibraTech (MVT)