

**KHE 3250 (600637420) 1 1/4" Combination hammer**  
**Plastic Carry Case**

Order no. 600637420  
EAN 4007430213051



Representative picture



- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibration in order to protect the user.
- Ergonomic housing shape for chiseling tasks without side handle.
- Vario (V)-electronics for working at customized speeds to suit various application materials.
- Metabo Long-life motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminum alloy: long-lasting and robust
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Cable-protecting ball joint for the best freedom of motion when working

## Technical values

### Parameters

Max. single blow energy (EPTA)	3.1 J
Amps	7.2 AMPS
Maximum impact rate	4470 BPM
Rated input power	800 W
Max. capacity in concrete with hammer drills	1 1/4 "
Max. capacity in masonry with core bits	3 1/4 "
Max. capacity in steel	1/2 "
Max. capacity in soft wood	1 3/8 "
No-load speed	0 - 1150 RPM
Revolutions at rated load	920 RPM
Bit retainer	SDS-plus
Collar diameter	1 31/32 "
Weight (without power cable)	7.5 lbs
Cable length	13 ft

### Vibration

Hammer drilling concrete	12.9 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Chiseling	10.9 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
 Metabo VibraTech (MVT) side handle  
 Drilling depth guide  
 Plastic carrying case