

KH 5-40 (600763620) 1 9/16" Combination Hammer Plastic Carry Case

Order no. 600763620
EAN 4007430331861



Representative picture



- Combination hammer with 2 functions: hammer drilling, drilling, and chiseling
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Robust die cast aluminum gear housing for optimum heat dissipation and durability

Technical values

Parameters

Max. single blow energy (EPTA)	7.1 J
Amps	10 AMPS
Maximum impact rate	2800 BPM
Max. capacity in concrete with hammer drills	1 9/16 "
Max. capacity in masonry with core bits	4 1/8 "
No-load speed	620 RPM
Bit retainer	SDS-max
Collar diameter	2.4 "
Weight (without power cable)	15.7 lbs
Cable length	8.2 ft

Vibration

Hammer drilling concrete	16.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	13.3 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	95 dB(A)
Sound power level (LwA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

rubber-coated handle
 Drilling depth guide
 Lubricant for tool shank end
 Plastic carrying case