

## STA 18 LTX 100 (601002890) Cordless Jigsaw 18V; Cardboard box

Order no. 601002890 EAN 4007430324603



Representative picture











- Extremely handy due to small handle size and soft-grip surface
- Precise and material-matched sawing due to the variable stroke rate, pendulum stroke and low-lying saw blade guidance with spring support
- Metabo "Quick" for changing saw blades without tools and with automatic ejection
- Selectable shaving blower function ensures free view of cutting line
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: www.cordless-alliance-system.com

www.metabo.com 1/2



| Technical values              |                |  |
|-------------------------------|----------------|--|
| Parameters                    |                |  |
| Battery voltage               | 18 V           |  |
| Cutting depth wood            | 4 "            |  |
| Cutting depth NF metal        | 1"             |  |
| Cutting depth sheet steel     | 3/8 "          |  |
| Swivel range from / to:       | - 45 / + 45 °  |  |
| Pendulum stroke levels        | 4              |  |
| Strokes – no load             | 550 - 2800 RPM |  |
| Saw blade stroke              | 7/8 "          |  |
| Weight without battery pack   | 4.2 lbs        |  |
| Weight including battery pack | 5.1 lbs        |  |
| Vibration                     |                |  |
| Sawing wood                   | 8.8 m/s²       |  |
| Uncertainty of measurement K  | 1.5 m/s²       |  |
| Sawing metal                  | 11.8 m/s²      |  |
| Uncertainty of measurement K  | 1.5 m/s²       |  |
| Noise emission                |                |  |
| Sound pressure level          | 83 dB(A)       |  |
| Sound power level (LwA)       | 94 dB(A)       |  |
| Uncertainty of measurement K  | 3 dB(A)        |  |

## Scope of delivery

Extraction nozzle

Protective glass

Chip guard plate

Hexagonal wrench

without battery pack, without charger

www.metabo.com 2/2