

## **KHE D-26 (601109420) 1" Combination hammer** **Plastic Carry Case**

Order no. 601109420

EAN 4007430305282



Representative picture



- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Spade handle for the best working comfort and maximum productivity when working low down or above the head
- Vario (V)-electronics for working at customized speeds to suit various application materials.
- High performance hammer action, precisely mounted in a housing made of aluminum alloy: long-lasting and robust
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Lockable switch for trouble-free working in continuous operation
- Frame hook for easily and securely storing hammers on frames and ladders

## Technical values

### Parameters

Max. single blow energy (EPTA)	2.3 J
Amps	7 AMPS
Maximum impact rate	5400 BPM
Rated input power	800 W
Max. capacity in concrete with hammer drills	1 "
Max. capacity in masonry with core bits	2 5/8 "
Max. capacity in steel	1/2 "
Max. capacity in soft wood	1 3/16 "
No-load speed	0 - 1150 RPM
Revolutions at rated load	960 RPM
Bit retainer	SDS-plus
Collar diameter	1 11/16 "
Weight (without power cable)	6.4 lbs
Cable length	13 ft

### Vibration

Hammer drilling concrete	13.7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Chiseling	15 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	87 dB(A)
Sound power level (LwA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
 Side Handle  
 Drilling depth guide  
 Plastic carrying case