

## STA 18 LTX 140 (601405890) Cordless Jigsaw 18V; Cardboard box

Order no. 601405890  
EAN 4007430236944



Representative picture



- Extremely powerful jigsaw with VTC electronics for fast cuts into soft wood of up to 140 mm
- High sawing performance: in excess of 40 metres in chipboard (19 mm) with only one battery pack charge
- Extremely handy due to small handle size and soft-grip surface
- Precise and material-matched sawing due to the variable stroke rate, pendulum stroke and low-lying saw blade guidance with spring support
- Metabo "Quick" for changing saw blades without tools and with automatic ejection
- Convenient automatic start: automatic soft start stroke acceleration
- Simple bevel cuts thanks to tool-less adjustable footplate with rest points
- Selectable shaving blower function ensures free view of cutting line
- Integrated LED work light for illumination of the cutting line
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for working at customized strokes to suit the application material and speeds that remain almost constant, even under load
- Restart protection: prevents unintentional start-up after battery replacement
- Long service life thanks to optimum gear and motor design and robust die-cast aluminum gear housing.
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical values

### Parameters

Type of battery pack	LiHD
Battery voltage	18 V
Cutting depth wood	5 1/2 "
Cutting depth NF metal	1 3/8 "
Cutting depth sheet steel	3/8 "
Swivel range from / to:	- 45 / + 45 °
Pendulum stroke levels	4
Strokes – no load	1000 - 3000 RPM
Saw blade stroke	1 1/32 "
Weight without battery pack	5.1 lbs
Weight including battery pack	6 lbs

### Vibration

Sawing wood	12 m/s <sup>2</sup>
Uncertainty of measurement K	1.8 m/s <sup>2</sup>
Sawing metal	12 m/s <sup>2</sup>
Uncertainty of measurement K	2.3 m/s <sup>2</sup>

### Noise emission

Sound pressure level	90 dB(A)
Sound power level (LwA)	101 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Plastic guard plate  
Chip guard plate  
without battery pack, without charger