

## KH 18 LTX BL 28 Q (601715840) Cordless Hammer 18V; metaBOX 165 L; with Metabo Quick Chuck

Order no. 601715840  
EAN 4061792218611



Representative picture



- Extremely lightweight and easy to handle cordless hammer with integrated suction interface
- Maximum drilling power, efficiency, and service life with brushless technology and high-performance hammer action
- Dust-free drilling with compact dust extraction ISA 28 (accessory)
- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Metabo VibraTech (MVT): healthy, low-fatigue work, even in continuous use
- Metabo Quick: fast drill chuck exchange without tools for working with SDS-plus and straight shank drills
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Optional speed and impact energy reduction for working on softer materials
- Electronic soft start for precise spot-drilling
- Twice as safe during drill bit blocking: no kick-back, thanks to mechanical decoupling, plus lightning-fast, sensor-controlled shut-down
- LED work light for optimal view of the drilling site
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical values

### Parameters

|  |              |
|--|--------------|
| Battery voltage                              | 18 V         |
| Max. single blow energy (EPTA)               | 3 J          |
| Maximum impact rate                          | 4470 BPM     |
| Max. capacity in concrete with hammer drills | 1 3/32 "     |
| Max. capacity in masonry with core bits      | 3 7/32 "     |
| Max. capacity in steel                       | 1/2 "        |
| Max. capacity in soft wood                   | 1 3/16 "     |
| No-load speed                                | 0 - 1000 RPM |
| Bit retainer                                 | SDS-plus     |
| Weight without battery pack                  | 7.5 lbs      |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 18.2 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Chiseling                    | 13.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LwA)      | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
 Keyless chuck for tools with cylindrical shank end  
 rubber-coated handle  
 Drilling depth guide  
 metaBOX 165 L  
 without battery pack, without charger