

## WPB 18 LT BL 11-150 Quick (601737830) 6" Cordless Angle Grinder 18V; Cardboard box; with brake, quick-locking nut

Order no. 601737830  
EAN 4061792228610



Representative picture



- New generation brushless cordless angle grinder: as powerful as a plug-in, 1100 Watt tool thanks to 40% more power
- Maintenance-free brushless motor with outstanding efficiency and an extremely easy to handle design
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Quick braking system for the highest level of User Safety stops the disc in seconds after switching off
- M-Quick System for disc change without tools at the push of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be turned in 90° steps for excellent ergonomics in every working position
- Metabo S-automatic Torque Safety Clutch: minimizes kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety
- Restart protection: prevents unintentional start-up after battery replacement
- Detachable dust filter protects motor from coarse particles
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical values

### Parameters

|                               |               |
|-------------------------------|---------------|
| Battery voltage               | 18 V          |
| Disc diameter                 | 6 "           |
| Max. cutting depth            | 1.811 "       |
| No-load speed                 | 10000 RPM     |
| Spindle thread                | 5/8" - 11 UNC |
| Grip circumference            | 6.299 "       |
| Weight without battery pack   | 3.97 kg       |
| Weight including battery pack | 2.5 kg        |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 8.8 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 81 dB(A) |
| Sound power level (LwA)      | 92 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Clip-on cutting wheel guard 6"  
 2 guards (4 1/2" and 6")  
 Inner support flange  
 M-Quick flange nut  
 Side Handle  
 Dust Protection Filter  
 without battery pack, without charger