

## KFM 18 LTX 3 RF (601754840) Cordless Metal Bevelling Tool 18V; metaBOX 215

Order no. 601754840  
EAN 4007430291462



Representative picture



- Most powerful cordless metal bevelling tool for 45° chamfers up to 4 mm and radii of 2 and 3 mm
- Surfaces free from oxide and burrs as ideal preparation for the application of powder or paint coatings for maximum protection from corrosion
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1 steps; stop points for short setting times, and protection against unintentional adjustment of the cutting depth when working
- Slim cutter head and ball bearing stationary seal ring for working in tubes and in curves
- Guide stop for uniform finish and high quality of the surface when processing straight sheets
- Bail handle adjusts without tools for secure, even guiding
- Battery pack can be swiveled for better working in hard to reach places.
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery replacement
- Detachable dust filter protects motor from coarse particles
- With metaBOX, the smart solution for transportation and storage
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical values

### Parameters

Type of battery pack	Li-Power
Battery voltage	18 V
No-load speed	7000 RPM
Type of edges	chamfer and radius
Max. chamfer width 45°	1/4 "
Max. chamfer height at 45°	5/32 "
Possible radii	R2 / R3
Grade cutting depth setting	0.00394 "
Curvature smallest internal Ø	13 mm
Weight without battery pack	5.3 lbs
Weight including battery pack	6.8 lbs

### Vibration

Vibration	0.94 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	84 dB(A)
Sound power level (LwA)	95 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

2 Carbide indexable inserts 45° chamfer  
 2 Carbide indexable inserts radius R2  
 2 Carbide indexable inserts radius R3  
 Guide Stop  
 Screwdriver for Torx screws 15  
 Bow type handle  
 Dust Protection Filter  
 metaBOX 215  
 without battery pack, without charger