

## GB 18 LTX BL Q I (602362840) Cordless Tapper 18V; metaBOX 145 L

Order no. 602362840  
EAN 4061792188204



Representative picture



- Fully-featured, powerful cordless drill for demanding applications with unique, patented thread-tapping function
- Quick and interruption-free drilling and cleaning of threads thanks to automatic change of the direction of rotation
- Quick-change threaded chuck for mounting square and straight shank drills
- Long service life and long tool life of the screw tap through intelligent torque monitoring
- Metabo Quick System: quickly exchange chucks, bit holders, angle adapters and more for flexible work
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Selectable "impulse" mode for removal of damaged screws and for spot-drilling on smooth surfaces
- Precision Stop: Electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Electronic safety shutdown of the motor: no kickback if the drill stops unexpectedly- for good user safety
- With handy belt hook and bit holder, can be fixed either on the right or left side
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical values

### Parameters

Battery voltage	18 V
Maximum torque, soft	575 in-lbs
Pulse torque	575 in-lbs
Maximum torque, hard	1151 ft. lbs
Adjustable torque	9 - 177 in-lbs
Max. thread diameter	M 12 (1/2" UNC/UNF)
Max. capacity in steel	1/2 "
Max. capacity in soft wood	2.68 "
No-load speeds	0 - 550 / 0 - 2000 RPM
Chuck capacity	1/32 - 1/2 "
Collar diameter	1 11/16 "
Weight without battery pack	4 lbs
Weight including battery pack	4.9 lbs

### Vibration

Drilling in metal	2.2 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	76 dB(A)
Sound power level (LwA)	87 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Quick change tapping chuck M4-M6  
 Quick change tapping chuck M8-M12  
 Side Handle  
 Belt hook with bit case  
 metaBOX 145 L