

## GB 18 LTX BL Q I (602362840) Cordless Tapper 18V; metaBOX 145 L

Order no. 602362840 EAN 4061792188204



Representative picture

















- High-grade cordless drill/screwdriver with unique, patented thread-tapping function
- Quick and interruption-free drilling and cleaning of threads thanks to automatic change of the direction of rotation
- Quick-change threaded chuck for mounting square and straight shank drills
- Long service life and long tool life of the screw tap through intelligent torque monitoring
- Metabo "Quick" System: Quick change of tool holder and bits, ideal for fast and convenient change of applications
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Selectable "impulse" mode for removal of damaged screws and for spot-drilling on smooth surfaces
- Precision Stop: Electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Electronic safety shutdown of the motor: no kickback if the drill stops unexpectedly- for good user safety
- With handy belt hook and bit holder, can be fixed either on the right or left side
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: www.cordless-alliance-system.com

www.metabo.com 1/2



Technical values		
Parameters		
Battery voltage	18 V	
Maximum torque, soft	575 in-lbs	
Pulse torque	575 in-lbs	
Maximum torque, hard	1151 ft. lbs	
Adjustable torque	9 - 177 in-lbs	
Max. thread diameter	M 12 (1/2" UNC/UNF)	
Max. capacity in steel	1/2 "	
Max. capacity in soft wood	2.68 "	
No-load speeds	0 - 550 / 0 - 2000 RPM	
Chuck capacity	1/32 - 1/2 "	
Collar diameter	1 11/16 "	
Weight without battery pack	4 lbs	
Weight including battery pack	4.9 lbs	
Vibration		
Drilling in metal	2.2 m/s <sup>2</sup>	
Uncertainty of measurement K	1.5 m/s <sup>2</sup>	
Noise emission		
Sound pressure level	76 dB(A)	
Sound power level (LwA)	87 dB(A)	
Uncertainty of measurement K	3 dB(A)	

## Scope of delivery

Quick change tapping chuck M4-M6 Quick change tapping chuck M8-M12 Side Handle Belt hook with bit case metaBOX 145 L

www.metabo.com 2/2