

## BS 18 LTX-3 BL Q I Metal (603180620) Cordless Drill / Driver 18V 2x5.5Ah LiHD; Charger ASC 145; metaBOX 145 L

Order no. 603180620

EAN 4061792211674



Representative picture



- Brushless 3-speed cordless drill with maximum power, ideal for demanding metalworking applications
- Extremely powerful chuck with retightening function prevents the tool insert from slipping and delivers the highest concentricity
- 3 speeds with high speed (max. 4,000/min) for expanded range of use and even faster drilling progress, especially in metal
- Metabo QuickPlus System: Quick change of bit retainer and bits, for flexible work at maximum load
- Precision Stop: Electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Euro collar (43 mm diameter) for diverse applications
- Electronic safety shutdown of the motor: no kickback if the drill stops unexpectedly- for good user safety
- Integrated LED work light with afterglow function for optimal brightness in the working area
- With handy belt hook and bit case, can be fixed either on the right or left side
- With metaBOX, the smart solution for transportation and storage
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

## Technical values

### Parameters

Type of battery pack	LiHD
Battery voltage	18 V
Battery capacity	2 x 5.5 Ah
Maximum torque, soft	575 in-lbs
Maximum torque, hard	1150 in-lbs
Adjustable torque	8.9 - 159.3 in-lbs
Max. capacity in steel	5/8 "
Max. capacity in soft wood	2.68 "
No-load speeds	0 - 450 / 0 - 2000 / 0 - 4000 RPM
Chuck capacity	1/16 - 1/2 "
Collar diameter	1.69 "
Weight without battery pack	4.4 lbs
Weight including battery pack	6.6 lbs

### Vibration

Drilling in metal	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	75 dB(A)
Sound power level (LwA)	85 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Futuro Top "QuickPlus" quick-change chuck  
 Side Handle  
 Adjustable wrench  
 2 LiHD Battery Packs (18 V/5.5 Ah)  
 "AIR COOLED" quick charger ASC 145  
 metaBOX 145 L