

WPB 13-150 Quick DS (603645420) Angle Grinder Cardboard box

Order no. 603645420 EAN 4061792176775



Representative picture


















- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Fastest brake system for the highest user protection: patented, mechanical disc brake stops the disc after switching off within 2 seconds, even in the event of a power cut
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



| Technical values | |
|------------------------------|----------------------|
| Parameters | |
| Amps | 12 AMPS |
| Disc diameter | 6" |
| Output power | 850 W |
| No-load speed | 10000 RPM |
| Speed at rated load | 7000 RPM |
| Torque | 33.6 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Weight (without power cable) | 6 lbs |
| Cable length | 8 ft |
| Vibration | |
| Surface grinding | 6.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 3 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 93 dB(A) |
| Sound power level (LwA) | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard

Clip-on Cutting Wheel Guard

Inner support flange

Spanner wrench

M-Quick flange nut

Side handle Metabo VibraTech (MVT)

www.metabo.com 2/2