

WEPB 24-230 MVT (606479420) Angle Grinder Cardboard box; with mechanical disc brake

Order no. 606479420 EAN 4007430337917



Representative picture















- Metabo Long-life motor with patented dust protection for long service life
- Highest user safety with mechanical disc brake and deadman switch: disc stops in 2.5 seconds after release, even during a power failure
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Rotating main handle and side handle can be mounted in 3 positions for optimal handle position, even while cutting
- Tool-free adjustable guard; twist-proof
- Starting Current Limitation with Soft Start prevents fuse being tripped upon start
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibration in order to protect the user.
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal on triggered restart protection or overheating

www.metabo.com 1/2



| Technical values | |
|------------------------------|----------------------|
| Parameters | |
| Amps | 15 AMPS |
| Disc diameter | 9 " |
| No-load speed | 6600 RPM |
| Speed at rated load | 4600 RPM |
| Torque | 150 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Grip circumference | 5.866 " |
| Weight (without power cable) | 13.2 lbs |
| Cable length | 13 ft |
| Vibration | |
| Surface grinding | 6.3 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard

Side handle Metabo VibraTech (MVT)

www.metabo.com 2/2