

## WEVF 10-125 Quick Inox (613080420) 5" Flat-Head Angle Grinder Cardboard box

Order no. 613080420  
EAN 4007430285126



Representative picture



- The most easy-to-handle flat-head angle grinder with speed regulation for perfect processing of stainless steel e.g. stockade fences
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Constamatic (VC)-Full wave electronics with thumbwheel for working with materials requiring customized speeds, which remain almost constant under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### Parameters

Amps	9.5 AMPS
Minimum accessible angle	43 °
Disc diameter	5 "
Rated input power	1000 W
Output power	550 W
No-load speed	2000 - 7600 RPM
Speed at rated load	6300 RPM
Torque	31 in-lbs
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	5.1 lbs
Cable length	8 ft
Grip circumference	7.594 "

### Vibration

Surface grinding	4.4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
 Inner support flange  
 Quick adjusting nut  
 Side Handle  
 1 Lamellar grinding disc Flexiamant Super Convex (125mm; P60)