

## WEPF 15-150 Quick (613084420) 6" Flat-Head Angle Grinder Cardboard box

Order no. 613084420 EAN 4007430285140



Representative picture



- Powerful flat-head angle grinder for working quickly in particularly acute angles down to 39°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Maximum cutting depth by means of a disc 6" in diameter
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT) side handle for vibration damping to protect the user's health
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

## Parameters

Amps	13.5 AMPS
Minimum accessible angle	39 °
Disc diameter	6 "
Rated input power	1550 W
Output power	900 W
No-load speed	9600 RPM
Speed at rated load	9600 RPM
Torque	35 in-lbs
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	6.2 lbs
Cable length	8 ft
Grip circumference	7 3/4 "
Vibration	
Surface grinding	6.8 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	3.4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Inner support flange

Quick adjusting nut

Side handle Metabo VibraTech (MVT)

1 Lamellar grinding disc Flexiamant Super Convex (150mm; P60)

1 Roughing disc Flexiamant Super FKS 60 (150x4mm; P60)