

## MT 18 LTX BL QSL (613088850) Cordless Multi-Tool 18V; Cardboard box

Order no. 613088850 EAN 4061792183957



Representative picture





- Oscillating cordless multi-tool with high performance comparable to that of a mains powered version
- For intensive interior development applications with precise fitting StarlockPlus 3D mount
- Indispensable for interior development work such as cutting, sanding, scraping and sanding of different materials
- Metabo Quick tool exchange: quick and convenient, with a magnetic mount for pre-fixing the tool
- Precise, dust-free work using a clamping ring with depth guide and suction connection (accessories)
- Unique brushless motor for the best possible efficiency while working, even in continuous mode
- Quick work progress thanks to a large oscillation angle and VTC electronics with a constant speed even under load
- Slim design and non-slip softgrip surfaces for optimized handling and comfort
- Extra bright LED lights for good visibility in the work area
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: www.cordless-alliance-system.com

www.metabo.com 1/2



Technical values	
Parameters	
Type of battery pack	Li-Power
Battery voltage	18 V
Orbital frequency with no load	8000 - 20000 RPM
Oscillation angle left/right	1.6 °
Bit retainer	Starlock/ StarlockPlus
Base plate, dimensions from corner to corner	3 5/8 "
Weight without battery pack	2.9 lbs
Weight including battery pack	3.7 lbs
Vibration	
Surface grinding	3.4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Sawing with plunge cut saw blade	19.9 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Sawing with segmented sawing blade	5.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	81 dB(A)
Sound power level (LwA)	92 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Plunge saw blade 32 mm (wood + metal) without battery pack, without charger

www.metabo.com 2/2