

## **B 32/3 (600323000) Drill**

### **Cardboard box**

Order no. 600323000

EAN 4007430172204



Product may differ from Image



- Powerful three-speed drill with extra high torque for working in a drill stand
- Robust mechanical gearbox with oil bath lubrication
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- For easy drilling of larger diameters and driving in of very long screws

**Technical data****Characteristics**

|                                 |                                 |
|---------------------------------|---------------------------------|
| Rated input power               | 1750 W                          |
| Output power                    | 1200 W                          |
| Drill Ø steel                   | 32 mm                           |
| Drill-Ø soft wood               | 70 mm                           |
| No-load speed                   | 0 - 170 / 0 - 320 / 0 - 470 rpm |
| Speed at rated load             | 110 / 190 / 280 rpm             |
| Gears                           | 3                               |
| Maximum torque                  | 190 / 120 / 90 Nm               |
| Collar diameter                 | 65 mm                           |
| Drill spindle with inside taper | MT 3                            |
| Weight (without power cable)    | 7.8 kg                          |
| Cable length                    | 5 m                             |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 90 dB(A)  |
| Sound power level (LwA)      | 101 dB(A) |
| Uncertainty of measurement K | 5 dB(A)   |

**Scope of delivery**

Drift key