

## WEPBA 19-180 Quick RT (601099000) Angle grinder Cardboard box

Order no. 601099000  
EAN 4007430314277



Product may differ from Image



- The most powerful one with full 1,900 Watt for industrial processing of weld seams and a cutting depth like a large angle grinder (Ø 230 mm) with only half the weight
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Marathon-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest degree of user safety thanks to patented, mechanical disc brake and deadman's switch: disc stop in 2 seconds after releasing even in case of a power cut
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

## Characteristics

Disc-Ø	180 mm
Rated input power	1900 W
Output power	1240 W
No-load speed	8200 rpm
Speed at rated load	8200 rpm
Torque	5 Nm
Spindle thread	M 14
Handle circumference	138 mm
Weight (without power cable)	2.9 kg
Cable length	4 m

## Vibration

Surface grinding	4.9 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

## Noise emission

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
Inner support flange  
M-Quick flange nut  
Metabo VibraTech (MVT) side handle