

## STEB 140 Plus (601404500) Jigsaw metaBOX 145

Order no. 601404500  
EAN 4007430212252



Product may differ from Image



- Extremely powerful jigsaw with VTC-Electronics for fast cuts into soft wood of up to 140 mm deep
- Precise and material-matched sawing due to the variable stroke rate, pendulum stroke and low-lying saw blade guidance with spring support
- Metabo Quick for tool-free saw blade change and with automatic ejection
- Convenient auto start with automatic stroke rate acceleration
- Simple bevel cuts thanks to footplate with rest points that can be adjusted without tools
- Selectable chip blowing function ensures free view of cutting line
- Motion-controlled LED work light for optimum illumination of the cutting line
- Vario Tacho Constamatic (VTC) Full-wave Electronics for work with materials requiring customised stroke rates, which remain constant under load
- Restart protection: prevents unintentional start-up after power supply interruption
- Long service life thanks to optimum gear and motor design and robust die-cast aluminium gear housing
- With metaBOX, the intelligent solution for transport and storage

## Technical data

### Characteristics

|                              |                 |
|------------------------------|-----------------|
| Rated input power            | 750 W           |
| Output power                 | 420 W           |
| Cutting depth wood           | 140 mm          |
| Cutting depth NF metal       | 35 mm           |
| Cutting depth sheet steel    | 10 mm           |
| Swivel range from / to:      | - 45 / + 45 °   |
| Pendulum stroke levels       | 4               |
| Strokes in idle              | 1000 - 3100 rpm |
| Saw blade stroke             | 26 mm           |
| Weight (without power cable) | 2.6 kg          |
| Cable length                 | 4 m             |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Sawing wood                  | 10.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Sawing metal                 | 8.4 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 90 dB(A)  |
| Sound power level (LwA)      | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Extraction Nozzles  
 Protective glass  
 Plastic guard plate  
 Chip Guard Plates  
 metaBOX 145