

WE 24-230 MVT (606469260) Angle grinder Cardboard box; with rotating main handle, deadman switch

Order no. 606469260 EAN 4007430268211



Product may differ from Image













- Metabo Marathon motor with patented dust protection for long service life
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Deadman's switch for high user protection
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

www.metabo.com 1/2



| Technical data | |
|------------------------------|----------------------|
| Characteristics | |
| Disc-Ø | 230 mm |
| Rated input power | 2400 W |
| Output power | 1600 W |
| No-load speed | 6600 rpm |
| Speed at rated load | 4600 rpm |
| Torque | 17 Nm |
| Spindle thread | M 14 |
| Handle circumference | 144 mm |
| Weight (without power cable) | 5.8 kg |
| Cable length | 4 m |
| Vibration | |
| Surface grinding | 6.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard

Inner support flange

Nut with two holes

Metabo VibraTech (MVT) side handle

Flat-pin spanner

www.metabo.com 2 / 2