

## W 26-230 MVT (606474000) Angle grinder Cardboard box; with rotating main handle

Order no. 606474000 EAN 4007430268297



Product may differ from Image





- Metabo Marathon motor with patented dust protection for long service life
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1 / 2



| Technical data               |                      |
|------------------------------|----------------------|
| Characteristics              |                      |
| Disc-Ø                       | 230 mm               |
| Rated input power            | 2600 W               |
| Output power                 | 1800 W               |
| No-load speed                | 6600 rpm             |
| Speed at rated load          | 4800 rpm             |
| Torque                       | 18 Nm                |
| Spindle thread               | M 14                 |
| Handle circumference         | 144 mm               |
| Weight (without power cable) | 6.3 kg               |
| Cable length                 | 4 m                  |
| Vibration                    |                      |
| Surface grinding             | 6.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Noise emission               |                      |
| Sound pressure level         | 94 dB(A)             |
| Sound power level (LwA)      | 105 dB(A)            |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard

Inner support flange

Nut with two holes

Metabo VibraTech (MVT) side handle

Flat-pin spanner

www.metabo.com 2 / 2