

BE 75-16 (600580000) Drill Cardboard box

Order no. 600580000 EAN 4007430201737



Product may differ from Image



- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Suitable for powerful drilling of larger diameters and for stirring thick, liquid-like materials

www.metabo.com 1/2



Technical data	
Characteristics	
Rated input power	750 W
Output power	470 W
Drill Ø steel	16 mm
Drill-Ø soft wood	50 mm
No-load speed	0 - 660 rpm
Speed at rated load	350 rpm
Gears	1
Maximum torque	75 Nm
Collar diameter	43 mm
Chuck capacity	1.5 - 13 mm
Drill spindle with hexagonal recess	6.35 mm
Drill spindle thread	1/2 " - 20 UNF
Weight (without power cable)	2.6 kg
Cable length	4 m
Vibration	
Drilling in metal	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	81 dB(A)
Sound power level (LwA)	92 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Geared chuck

Chuck key

long side handle

www.metabo.com 2/2