

Product may differ from Image

HWW 3300/25 G (600968000) Domestic waterwork Cardboard box

Order no. 600968000 EAN 4007430239587



STOP

- For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Pressure vessel for energy-saving and low-noise provision of water
- Pressure switch at the tank for automatic activation in case of increased water demand
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Separate water filling opening for simple operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- For garden irrigation with 1 or 2 sprinklers
- For single phase alternating current

Technical data

Characteristics

| Rated input power | 900 W |
|------------------------------|--------------------|
| Maximum delivery rate | 3300 l/h |
| Maximum delivery height | 45 m |
| Maximum pressure | 4.5 bar |
| Maximum suction height | 8 m |
| Switch-on pressure approx. | 1.4 bar |
| Switch-off pressure approx. | 3.2 bar |
| Suction port | 1" female thread |
| Discharge port | 1" female thread |
| Tank capacity, approximately | 24 |
| Pump housing | Grey cast iron |
| Protection type IP | IP X4 |
| Drive shaft | Stainless steel |
| Tank | Steel |
| Number of impellers | 1 |
| Dimensions | 485 x 275 x 585 mm |
| Weight | 16.2 kg |
| Cable length | 1.5 m |
| Noise emission | |
| Sound pressure level | 66 dB(A) |
| Sound power level (LwA) | 78.4 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Check Valve Fabric Sealing Tape