

## Basic 250-24 W (601533000) Compressor

### Cardboard box

Order no. 601533000  
EAN 4007430244420



Product may differ from Image



- Powerful, robust compressor for simple, commercial use
- Oil-lubricated Piston Condenser
- For single phase alternating current
- Operating pressure can be regulated according to application by means of a pressure reducer and manometer
- Convenient pressure switch for good cold starting, complete with relief valve
- Overload protection: protects the motor from overheating
- Rubberised, stable wheels for mobile use
- Additional manometer for displaying the tank pressure
- Rubber-coated handle for comfortable handling
- 10 year tank warranty against rust

**Technical data****Characteristics**

Suction rate	200 l/min
Filling capacity	110 l/min
Effective delivery volume (at 80% max. pressure)	95 l/min
Maximum pressure	8 bar
Rated input power	1.5 kW
Maximum speed	2850 rpm
Tank capacity	24 l
Sound pressure level (LpA)	81 dB(A)
Sound power level (LwA)	97 dB(A)
Dimensions	620 x 340 x 580 mm
Weight	27 kg
Cable length	1.5 m

**Noise emission**

Sound pressure level	81 dB(A)
Sound power level (LwA)	97 dB(A)

**Scope of delivery**

Universal quick-action coupling  
Pull handle with rubber-grip